

## ACCESORIES FOR ROTATIONAL VISCOMETERS

# APM and APM/B

## Small Sample Adapters

### APM and AMP/B

APM or small sample adapter and APM/B or small sample adapter without flow jacket consist of an accessory with a cylindrical sample chamber and spindles which allows accurate viscosity measurements with small volumes. (It is supplied without spindles).

Its rheologically correct cylindrical geometry allows extremely accurate viscosity measurements and shear rate and shear stress determinations.



Viscometer type	Measuring range (cP)
L	2 - 200.000
R	38 - 3.300.000
H	3 - 266.000 Poise

ViscoPad series



EVO series



Master series



Viscolead series



## Technical features for APM

- Stainless steel sample chamber, removable and easily cleaned.
- Flow jacket that allows thermostatisation of the sample between -10 a +100°C (14 a 212 °F).
- Under request: special flow jacket for reaching temperatures above 200°C.
- Sample volume: from 8 to 13 ml, depending on the spindle used.
- PT100 probe to determine the sample temperature with accuracy (optional).

## Technical features for APM/B

- Stainless steel sample chamber, removable and easily cleaned.
- Sample volume: from 8 to 13 ml, depending on the spindle used.
- PT100 probe to determine the sample temperature with accuracy (optional).

Viscometer type	Measuring range (cP)
L	2 - 200.000
R	38 - 3.300.000
H	3 - 266.000 Poise



APM



APM



APM CASE



APM/B



APM/B



APM CASE/B

## Leading Viscosity Technology