



JULABO MB Heating Immersion Circulator

Heating Immersion Circulator for any bath tanks up to 20 liters

JULABO Heating Immersion Circulators are available for various bath tanks up to a capacity of 50 litres and come equipped with a bath clamp that fits onto all tanks with a wall thickness up to 26 mm. This clamp allows fast and problem-free assembling for existing as well as new bath tanks. The immersion depth is 16.5 cm (adjustable down to 14.5 cm). The immersed parts are made of high-quality stainless steel or plastic. The pump set, which is available as an accessory, provides pumping to external systems for provision of external temperature tasks. An integrated cooling coil for cooling-water connection is also available as an accessory.

Available downloads:

- ➔ [EasyTemp Software](#)
- ➔ [Interactive product demo](#)
- ➔ [Easy BlackBox remote diagnosis software](#)



Features

- o MULTI-DISPLAY (LED) for actual and setpoint values, warning/safety functions and pump stage
- o Keypad for setpoints, warning/safety values and menu functions
- o PID2 temperature control with drift compensation
- o ATC3 3-Point-Calibration
- o Early warning system for low liquid level (DBGM 203 06 059.8)
- o Adjustable high temperature cut-out, visible via display
- o RS232 interface for online communication

Model		MB
JULABO Order No.		9140000
Working temp. range	°C	20 ... 100
Temperature controller		PID
Temperature stability	± °C	0.02
Display		LED
Display resolution	°C	0.1
Integrated Programmer		no
Heater capacity	W	2000

Pump

Pressure pump capacity max.	mbar	120
	l/min	10
Pump connections		-

Electrical connections

Digital interfaces	RS232	RS485	PROFIBUS
	X	-	-

General information

Dimensions (W x L x H)	cm	13 x 15 x 33
Weight	kg	3,3
Ambient temperature	°C	5...40
Mains power (±10%)	V/Hz	230V / 50-60Hz or 115V / 50-60Hz

		or 100V / 50-60Hz
Power / current consumption		n/a
Classification according to DIN 12876-1	Class	1 (NFL)

Miscellaneous

Installation cooling coil and pump set for external applications available as accessory.

Data determined at a mains voltage of 230V / 50-60Hz and ambient temperature of 20 °C.

Technical changes without prior notification reserved. Pictures may differ from original.

JULABO Labortechnik GmbH
D-77960 Seelbach / Germany
Telephone +49 7823/51-0 | Telefax +49 7823/2491
Email info@julabo.de