

Cubis[®] MCM60K3

Manual Mass Comparator

User Benefits

- Complete mass standard laboratory in a single unit
- Integrated climate sensors for recording all data relevant for determining measurement uncertainty
- Integrated workflow control for efficient and error-free mass comparison
- Fast measurement cycles according to the ABA, ABBA or AB₁...B_nA method



Highlighted Performance Features

- Cubis[®] MSA color touch screen for fast and simple configuration of parameters and workflows
- External sensor-equipped climate module for recording the temperature, humidity and air pressure
- Integrated calibration workflows for ABA, ABBA, AB₁...B_nA cycles to ensure efficient, error-free mass comparison
- Fully integrated function for determining the measurement uncertainty in accordance with OIML and ASTM recommendations
- Filters for optimal adaptation of the mass comparator to ambient conditions
- Monolithic weighing technology
- For display and evaluation, complete electronics and power supply separated from the weighing system to prevent heat from affecting the results
- All MCM mass comparators featuring eccentric (off-center) load compensation for easy loading of weights without automatic centering
- Additional applications for density determination, statistics and individual identifiers are integrated as standard programs
- Built-in SD card slot for storage and transfer of all data and settings
- Graphical level indicator for interactive user guidance during levelling
- Easy logging of reference weight data
- Continuous weighing range display: any weight between 0 g and the maximum capacity can be displayed
- USB, RS-232C and Ethernet interface ports to integrate the mass comparator into networks or to enable it to communicate with external software via third-party protocols, standardized communication protocols or Web services

Technical Specifications

Metrological Specifications	
Maximum capacity	64 kg
Application range	0 – 64 kg
Readability	2 mg
Repeatability, optimal ¹⁾	4 mg
Repeatability, standard E ²⁾	6 mg
Repeatability, E ¹ / ₁₀ load ²⁾	4 mg
Repeatability standard, F ³⁾	10 mg
Electronic weighing range and tare range	64 kg
Linearity	40 mg
Eccentric load deviation	3.5 mg mm
Stabilization time	5 s
Cycle time, ABBA in s	120 s

Basic Equipment	
Interfaces	RS232C USB LAN
Application programs	Basic weighing, mass unit conversion, individual identifiers, density determination, statistics
Below-comparator weighing port	With optional accessory
PC connecting cable	USB

Ambient Conditions	
Permissible operating temperature range	10–30 °C
Recommended operating temperature	22 °C
Temperature fluctuations	0.3°C/h 0.5°C/12h
Max. air current	< 0.2 m/s
Humidity range	40 – 70 %
Humidity fluctuations	5% 4 h
Power supply	100 – 240 V AC/50 – 60 Hz
Power consumption	< 35 VA

Dimensions	
Weighing pan dimensions (W × D)	400 × 300 mm
Sample size (D × H)	400 × 326 × 126 mm
Weigh cell (W × D × H)	239 × 320 × 56 mm
Electronic unit (W × D × H)	15 kg
Net weight	18.6 kg
Gross weight	1
Number of packages	73 × 60 × 36 cm
Optimal height for setup	800 mm

Applications	
OIML R111, class E1	
OIML R111, class E2	20 – 50 kg
OIML R111, class F1	2 – 50 kg
OIML R111, class F2	1 – 50 kg
OIML R111, class M1	200 g – 50 kg
OIML R111, class M2	
OIML R111, class M3	
ASTM E617, class 0	10 – 50 kg
ASTM E617, class 1	5 – 50 kg
ASTM E617, class 2	3 – 50 kg
ASTM E617, class 3	2 – 50 kg
ASTM E617, class 4	
ASTM E617, class 5	
ASTM E617, class 6	

Optional Accessories	
External calibration weight	50 kg E2 YCW752-00
Climate module, uncalibrated, for all MCM models	YCM20MC
Calibration of a YCM20MC climate module with DAkkS calibration certificate	YCM20DAkkS
Climate module with DAkkS calibration certificate for all MCM models	YCM20MC-DAkkS
Tower for climate module, for connection to MCM high-capacity models, including cable	YCM20MC-Tower
Optional draft shield	YDS05C YDS03C
Hook for below-comparator weighing	69EA0040
Lifting device for 10 kg	YAW51
Lifting device for 20 kg	YAW52
Lifting device for 50 kg	YAW53

The standard deviation "s" is the repeatability calculated from 5 ABA cycles under the following conditions:

- ¹⁾ Optimal conditions: automatic measurement without operator influence measured in a laboratory under E1 conditions, on a decoupled weighing stone no drafts from above
- ²⁾ Standard conditions E: measured by hand in a laboratory under E1 conditions, on a decoupled weighing stone; no drafts from above
- ³⁾ Standard conditions F: measurement performed manually in a laboratory under at least F1 conditions, on a non-decoupled weighing stone, air conditioning and minimal drafts from above